



Dongguan Baoxu Chemical Technology.,Ltd.

P:+86-0769-22821082 Fax:0769-22821083

Email:info@additivesforpolymer.com Web:www.additivesforpolymer.com

8th Chenwu East Road, Houjie Town, Dongguan City, Guangdong Province, China

BX ATA P100

Physical and chemical properties

Item	BX ATA PA100
Form	Solid, without carrier
Color	White to Light yellow color
Melting Point °C	> 90
Surface resistivity (25 °C, 50%R.H.) [ohms/sq.]	10 ⁷
Application	Polyolefin, PP, PE, TPO, HDPE

Application

Polyolefin including PP, PE, TPO, HDPE.

Advantage

- No migrating side effects.
- for both anti-dust and static dissipative applications.
- maintain mechanical properties of the polymer.
- easy processed by extrusion or injection process.
- odorless
- light color.
- halogen-free.
- long-lasting performance

Dosage

7-15% based on polymer and applications.

Handling

- BX ATA P100 product is very hygroscopic substance which is dried before shipping. Store in original container securely under cool and dry conditions. After opening, use immediately.
- Keep closed when not in use. In case of that this product absorbs moisture, drying at 70-80 °C for 3h under vacuum is required before use

The information and statement herein are believed to be reliable but are not to be construed as a warranty or representation for which we assume legal responsibility, Users should undertake sufficient verification and testing to determine the suitable for their own particular purpose of any information or products referred to herein. No warranty of fitness for a particular purpose is made.